

TECHNICAL INFORMATION

ROTOR NOZZLES

HUNTER I-20

Standard Nozzles

Nozzle	Pressure PSI	Radius Ft.	Flow GPM
1.0	30	30'	.9
	40	31'	1.0
	50	31'	1.2
	60	32'	1.3
1.5	30	32'	1.2
	40	33'	1.4
	50	34'	1.6
	60	34'	1.8
2.0	30	34'	1.6
	40	36'	1.8
	50	38'	2.0
	60	38'	2.2
3.0	30	36'	2.0
	40	38'	2.4
	50	40'	2.7
	60	40'	2.9

Standard Nozzles

Nozzle	Pressure PSI	Radius Ft.	Flow GPM
3.5	30	36'	2.6
	40	40'	3.0
	50	42'	3.4
	60	42'	3.7
4.0	30	37'	3.2
	40	40'	3.7
	50	43'	4.2
	60	44'	4.6
6.0	30	35'	4.2
	40	40'	4.9
	50	43'	5.5
	60	44'	6.0
8.0	30	41'	6.0
	40	44'	6.8
	50	45'	7.6
	60	47'	8.2

Data represents test results in zero wind. Adjust for local conditions. Radius may be reduced up to 25% with adjustment screw (this may alter the uniformity of the pattern).

Optimum performance is shown in bold type.